



RO3000 NATURAL EFFECT TOPCOAT

FIELD OF APPLICATION

Furniture, inner doors, inner claddings.

INFORMATION

It protects and decorates the wood, preventing any change of the natural aspect of the wood. Fast acting and easy to apply, it makes the wood highly water-repellent and smooth to the touch. It is possible to apply a third coat of Natural effect topcoat to guarantee a higher protection.

INSTRUCTIONS

Raw wood. Carefully clean the surface from dirt, grease, waxes and resins. Sand with 150-180 grit sandpaper and remove the powder. Apply 2-3 coats of Natural effect topcoat RO3000, at intervals of 1-2 hours. Between the coats, sand the surface with 320-400 grit sandpaper.

Coated wood. Sand with 80-150 grit sandpaper and remove the powder. Then proceed as indicated for the raw wood.

MAINTENANCE

Slightly sand with 220-320 grit sandpaper, remove the powder and apply one coat of RO3000. On the most deteriorated parts, apply a second coat.

OVERCOATING

Natural effect topcoat RO3000.

PACKAGING

0,5 L

2,5 L

-  Storage > 5°C
-  Painting > 10°C
-  Ready to use
-  Brush
Cloth
Roller
-  Yield 12-24 m²/L
-  Mix it well before use
-  Drying time between the coats 1-2 h
-  Final drying time 5 h
-  Solid content 18 ± 3 %
-  Viscosity DIN4 16 ± 3"
-  Specific weight 1,01 ± 0,1 g/cm³
-  pH 7,5 ± 0,5
-  Gloss level 5

